



# Dixon EZLink™ Armless Cam & Groove

*Push-to-connect, low profile, positive locking system and more!*



assembled with 6200 series elbow

patent pending

### Applications:

- transfer and/or unloading of fuels (gasoline or diesel) from tank truck to storage tanks
- transfer of liquids compatible with the available coupling and gasket materials

### Materials:

- couplings and dust caps: A356 aluminum, 316 stainless steel
- coupler tabs and springs: 316 stainless steel
- gaskets: Buna-N, Fluorosilicone (blue in color), or FKM (brown in color)

### Features:

- automatic couplers push-to-connect providing a reliable connection
- low profile allows easy connection and disconnection in tight applications
- coupler push tabs can be locked with safety pins and/or zip tie
- compatible with standard cam and groove adapters

### Specifications:

- refer to [dixonvalve.com](http://dixonvalve.com) for maximum crimp working pressure
- Buna-N gasket temperature range: **5°F to 180°F (-15°C to 82°C)**
- Fluorosilicone gasket temperature range: **-20°F to 180°F (-29°C to 82°C)**
- FKM gasket temperature range: **40°F to 200°F (4°C to 93°C)**



**Warning:** Only use EZLink™ gaskets and tabs for this coupling system. Traditional cam and groove handles and gaskets, or other types of seals are not compatible and will fail.

## Type B Coupler x Male NPT

| Size | A356 Aluminum<br>Part # | 316 Stainless Steel<br>Part # |
|------|-------------------------|-------------------------------|
| 1½"  | <b>EZL150-B-AL</b>      | <b>EZL150-B-SS</b>            |
| 2"   | <b>EZL200-B-AL</b>      | <b>EZL200-B-SS</b>            |
| 3"   | <b>EZL300-B-AL</b>      | <b>EZL300-B-SS</b>            |
| 4"   | <b>EZL400-B-AL</b>      | ---                           |



## Type C Coupler x King Crimp™ Hose Shank

| Size | A356 Aluminum Part # | 316 Stainless Steel Part # |
|------|----------------------|----------------------------|
| 1½"  | <b>EZL150-C-AL</b>   | <b>EZL150-C-SS</b>         |
| 2"   | <b>EZL200-C-AL</b>   | <b>EZL200-C-SS</b>         |
| 3"   | <b>EZL300-C-AL</b>   | <b>EZL300-C-SS</b>         |
| 4"   | <b>EZL400-C-AL</b>   | ---                        |



## Type D Coupler x Female NPT

| Size | A356 Aluminum Part # | 316 Stainless Steel Part # |
|------|----------------------|----------------------------|
| 1½"  | <b>EZL150-D-AL</b>   | <b>EZL150-D-SS</b>         |
| 2"   | <b>EZL200-D-AL</b>   | <b>EZL200-D-SS</b>         |
| 3"   | <b>EZL300-D-AL</b>   | <b>EZL300-D-SS</b>         |
| 4"   | <b>EZL400-D-AL</b>   | ---                        |



## Type DC Dust Caps

| Size | A356 Aluminum Part # | 316 Stainless Steel Part # |
|------|----------------------|----------------------------|
| 1½"  | <b>EZL150-DC-AL</b>  | <b>EZL150-DC-SS</b>        |
| 2"   | <b>EZL200-DC-AL</b>  | <b>EZL200-DC-SS</b>        |
| 3"   | <b>EZL300-DC-AL</b>  | <b>EZL300-DC-SS</b>        |
| 4"   | <b>EZL400-DC-AL</b>  | ---                        |



## Replacement Kits

- kit contains: 2 pins, 2 springs and 2 tabs

| Size            | Part #                                     |
|-----------------|--|
| 2"<br>3" and 4" | <b>EZL200RPLKIT</b><br><b>EZL300RPLKIT</b> |



## Replacement Gaskets

| Size | Buna-N Part #      | Fluorosilicone Part # | FKM Part #         |
|------|--------------------|-----------------------|--------------------|
| 1½"  | <b>EZL150-G-BU</b> | <b>EZL150-G-FV</b>    | <b>EZL150-G-VI</b> |
| 2"   | <b>EZL200-G-BU</b> | <b>EZL200-G-FV</b>    | <b>EZL200-G-VI</b> |
| 3"   | <b>EZL300-G-BU</b> | <b>EZL300-G-FV</b>    | <b>EZL300-G-VI</b> |
| 4"   | <b>EZL400-G-BU</b> | <b>EZL400-G-FV</b>    | <b>EZL400-G-VI</b> |



## Safety Clip

- clip is optional

| Plated Carbon Steel Part # |
|----------------------------|
| <b>EZLCL400</b>            |



## Dixon

800 High Street • Chestertown, MD 21620  
ph 877.963.4966 • fx 800.283.4966

[dixonvalve.com](http://dixonvalve.com)

